Product datasheet

Specifications

Green Premium™

W600 MODULAR DEVICE RAIL PRISMA G

03001

⊘ **Discontinued on:** 11 Jul 2022

⊘ **To be end-of-service on:** 31 Dec 2024

⊘ **Discontinued**

Price: 299.57 ZAR

Main

Range	Prisma
Range Of Product	Prisma G
Product Or Component Type	Rail
Accessory / Separate Part Category	Installation accessory
Range Compatibility	Prisma Prisma G Prisma Prisma Pack 250
Type Of Rail	Modular
Installed Device	Acti 9: fixed C120 without earth leakage protection - control: toggle TeSys: fixed GV2LE TeSys: fixed GV2ME TeSys: fixed GV2RTn Acti 9: fixed iC120 without earth leakage protection - control: toggle Vigilohm: IM20 Vigilohm: IM20H Vigilohm: fixed IM9 Vigilohm: fixed IM9-OL ComPact: fixed INS100 - control: direct front rotary handle - vertical installation ComPact: fixed INS160 - control: direct front rotary handle - vertical installation ComPact: fixed INS40 - control: direct front rotary handle - vertical installation ComPact: fixed INS63 - control: direct front rotary handle - vertical installation Acti 9: fixed modular device Multi9: fixed modular device Multi9: fixed NG125 without earth leakage protection - control: toggle Multi9: fixed NG125 NA - control: toggle Vigirex: RH10 Vigirex: RH21 Vigirex: RH99 Acti 9: fixed C120 with earth leakage protection - control: toggle Acti 9: fixed iC120 with earth leakage protection - control: toggle Multi9: fixed NG125 with earth leakage protection - control: toggle Acti 9: fixed 1/2 or 1 module lamp - horizontal installation ComPact: fixed INS125 - control: direct front rotary handle - vertical installation Acti 9: fixed measurement device - horizontal installation Multi9: fixed measurement device - horizontal installation Acti 9: fixed modular device <= 40 A Multi9: fixed modular device <= 40 A

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Life Is On | Schneider Electric

Poles Description	1 x 3P: fixed C120
	1 x 4P: fixed C120
	9 x 3P: fixed GV2LE
	9 x 3P: fixed GV2ME
	9 x 3P: fixed GV2RTn
	1 x 3P: fixed iC120
	1 x 4P: fixed iC120
	1 x 3P: fixed INS100 vertical installation
	1 x 4P: fixed INS100 vertical installation
	1 x 3P: fixed INS160 vertical installation
	1 x 4P: fixed INS160 vertical installation
	1 x 3P: fixed INS40 vertical installation
	1 x 4P: fixed INS40 vertical installation
	1 x 3P: fixed INS63 vertical installation
	1 x 4P: fixed INS63 vertical installation
	1 x 3P: fixed NG125
	1 x 4P: fixed NG125
	1 x 3P: fixed NG125 NA
	1 x 4P: fixed NG125 NA
	1 x 3P: fixed INS125 vertical installation
	1 x 4P: fixed INS125 vertical installation

Complementary

Installation Description	Floor-standing enclosure - width 600 mm
	Wall-mounted enclosure - width 600 mm
	Pack enclosure - width 600 mm

Life Is On | Schneider Electric

Number Of Vertical Modules [50 Mm]	2 module(s): 1/2 or 1 module lamp, direct in 600 mm Widefloor-standing enclosure
	2 module(s): 1/2 or 1 module lamp, direct in 600 mm Widewall-mounted enclosure
	5 module(s): C120 without earth leakage protection , direct in 600 mm Widefloor-standing enclosure
	5 module(s): C120 without earth leakage protection , direct in 600 mm Widewall-mounted enclosure
	3 module(s): GV2LE, direct in 600 mm Widefloor-standing enclosure
	3 module(s): GV2LE, direct in 600 mm Widewall-mounted enclosure
	3 module(s): GV2ME, direct in 600 mm Widefloor-standing enclosure
	3 module(s): GV2ME, direct in 600 mm Widewall-mounted enclosure
	3 module(s): GV2RTn, direct in 600 mm Widefloor-standing enclosure
	3 module(s): GV2RTn, direct in 600 mm Widewall-mounted enclosure
	5 module(s): iC120 without earth leakage protection , direct in 600 mm Widefloor-standing enclosure
	5 module(s): iC120 without earth leakage protection , direct in 600 mm Widewall-mounted enclosure
	3 module(s): IM20 in 600 mm Widefloor-standing enclosure
	3 module(s): IM20 in 600 mm Widewall-mounted enclosure
	3 module(s): IM20H in 600 mm Widefloor-standing enclosure
	3 module(s): IM20H in 600 mm Widewall-mounted enclosure
	3 module(s): IM9 in 600 mm Widefloor-standing enclosure
	3 module(s): IM9 in 600 mm Widewall-mounted enclosure
	3 module(s): IM9-OL in 600 mm Widefloor-standing enclosure
	3 module(s): IM9-OL in 600 mm Widewall-mounted enclosure
	4 module(s): INS100, direct in 600 mm Widefloor-standing enclosure
	4 module(s): INS100, direct in 600 mm Widewall-mounted enclosure
	5 module(s): INS100, direct in 600 mm Widefloor-standing enclosure
	5 module(s): INS100, direct in 600 mm Widewall-mounted enclosure
	4 module(s): INS125, direct in 600 mm Widefloor-standing enclosure
	4 module(s): INS125, direct in 600 mm Widewall-mounted enclosure
	5 module(s): INS125, direct in 600 mm Widefloor-standing enclosure
	5 module(s): INS125, direct in 600 mm Widewall-mounted enclosure
	4 module(s): INS160, direct in 600 mm Widefloor-standing enclosure
	4 module(s): INS160, direct in 600 mm Widewall-mounted enclosure
	5 module(s): INS160, direct in 600 mm Widefloor-standing enclosure
	5 module(s): INS160, direct in 600 mm Widewall-mounted enclosure
	4 module(s): INS40, direct in 600 mm Widefloor-standing enclosure
	4 module(s): INS40, direct in 600 mm Widewall-mounted enclosure
	4 module(s): INS63, direct in 600 mm Widefloor-standing enclosure
	4 module(s): INS63, direct in 600 mm Widewall-mounted enclosure
	2 module(s): measurement device, direct in 600 mm Widefloor-standing enclosure
	2 module(s): measurement device, direct in 600 mm Widewall-mounted enclosure
	2 module(s): measurement device, direct in 600 mm WidePack enclosure
	3 module(s): modular device <= 40 A, direct in 600 mm Widefloor-standing enclosure
	3 module(s): modular device <= 40 A, direct in 600 mm Widewall-mounted enclosure
	8 module(s): modular device <= 40 A, direct in 600 mm Widefloor-standing enclosure
	8 module(s): modular device <= 40 A, direct in 600 mm Widewall-mounted enclosure
	6 module(s): modular device <= 40 A, direct in 600 mm WidePack enclosure
	6 module(s): modular device, direct in 600 mm WidePack enclosure
	4 module(s): modular device, direct in 600 mm Widefloor-standing enclosure
	4 module(s): modular device, direct in 600 mm Widewall-mounted enclosure
	5 module(s): NG125 without earth leakage protection , direct in 600 mm Widefloor-standing enclosure
	5 module(s): NG125 without earth leakage protection , direct in 600 mm Widewall-mounted enclosure
	5 module(s): NG125 NA, direct in 600 mm Widefloor-standing enclosure
	5 module(s): NG125 NA, direct in 600 mm Widewall-mounted enclosure
	3 module(s): RH10, direct in 600 mm Widefloor-standing enclosure
	3 module(s): RH10, direct in 600 mm Widewall-mounted enclosure
	3 module(s): RH21, direct in 600 mm Widefloor-standing enclosure
	3 module(s): RH21, direct in 600 mm Widewall-mounted enclosure
	3 module(s): RH99, direct in 600 mm Widefloor-standing enclosure
	3 module(s): RH99, direct in 600 mm Widewall-mounted enclosure
	5 module(s): C120 with earth leakage protection , direct in 600 mm Widefloor-standing enclosure
	5 module(s): C120 with earth leakage protection , direct in 600 mm Widewall-mounted enclosure
	5 module(s): iC120 with earth leakage protection , direct in 600 mm Widefloor-standing enclosure
	5 module(s): iC120 with earth leakage protection , direct in 600 mm Widewall-mounted enclosure
	5 module(s): NG125 with earth leakage protection , direct in 600 mm Widefloor-standing enclosure
	5 module(s): NG125 with earth leakage protection , direct in 600 mm Widewall-mounted enclosure
9 Mm Pitches	48
Quantity Per Set	Set of 1

Height	52 mm
Width	468 mm
Depth	100 mm
Net Weight	0.24 kg
Colour	Natural
Material	Metal

Environment

Standards	IEC 61439-2 IEC 61439-1
Product Certifications	ASEFA

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	10 cm
Package 1 Length	46.5 cm
Package 1 Weight	240 g

Sustainability

Green Premium^{TM} label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Transparency   RoHS/REACh

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information   Yes

✓ Halogen Free Plastic Parts Product

Certifications & Standards

Eu Rohs Directive   Pro-active compliance (Product out of EU RoHS legal scope)

                                     EU RoHS Declaration

China Rohs Regulation   China RoHS declaration

                                     Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure   Product Environmental Profile