
Product datasheet

Specifications



MOUNTING PLATE NSX/CVS/ VIGI 630 V. FIX. ROT.HANDLE

03074

() Discontinued on: 19 May 2023

(!) Discontinued

Main

Range	Prisma
Range Of Product	Prisma G
Product Or Component Type	Mounting plate
Accessory / Separate Part Category	Installation accessory
Range Compatibility	Prisma Prisma G enclosure
Installation Description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm
Installed Device	EasyPact: fixed CVS400 without earth leakage protection - control: direct front rotary handle - vertical installation
	EasyPact: fixed CVS630 without earth leakage protection - control: direct front rotary handle - vertical installation
	ComPact: fixed NSX400 without earth leakage protection - control: direct front rotary handle - vertical installation
	ComPact: fixed NSX630 without earth leakage protection - control: direct front rotary handle - vertical installation
	EasyPact: fixed CVS400 with earth leakage protection - control: direct front rotary handle - vertical installation
	EasyPact: fixed CVS630 with earth leakage protection - control: direct front rotary handle - vertical installation
	ComPact: fixed NSX400 with earth leakage protection - control: direct front rotary
	handle - vertical installation ComPact: fixed NSX630 with earth leakage protection - control: direct front rotary handle - vertical installation
Poles Description	1 x 3P: fixed CVS400 vertical installation
	1 x 4P: fixed CVS400 vertical installation
	1 x 3P: fixed CVS630 vertical installation
	1 x 4P: fixed CVS630 vertical installation
	1 x 3P: fixed NSX400 vertical installation
	1 x 4P: fixed NSX400 vertical installation
	1 x 3P: fixed NSX630 vertical installation 1 x 4P: fixed NSX630 vertical installation
Condition Of Lloing Coble Tie	

Condition Of Using Cable Tie

Need additional plate (1M high) when installation of device is in vertical

Excluding VAT and subject to change. Please check with your local distributor through "Where to buy"

Product Certifications	ASEFA
Standards	IEC 61439-2
	in 600 mm Widewall-mounted enclosure (cable coming from top or bottom of enclosure)
	18 module(s): NSX630 with earth leakage protection , direct with long terminal shield
	in 600 mm Widefloor-standing enclosure (cable coming from top or bottom of enclosure)
	18 module(s): NSX630 with earth leakage protection , direct with long terminal shield
	enclosure)
	in 600 mm Widewall-mounted enclosure (cable coming from top or bottom of
	enclosure) 18 module(s): NSX400 with earth leakage protection , direct with long terminal shield
	in 600 mm Widefloor-standing enclosure (cable coming from top or bottom of
	18 module(s): NSX400 with earth leakage protection , direct with long terminal shield
	enclosure)
	in 600 mm Widewall-mounted enclosure (cable coming from top or bottom of
	18 module(s): CVS630 with earth leakage protection , direct with long terminal shield
	in 600 mm Widefloor-standing enclosure (cable coming from top or bottom of enclosure)
	18 module(s): CVS630 with earth leakage protection , direct with long terminal shield
	enclosure)
	in 600 mm Widewall-mounted enclosure (cable coming from top or bottom of
	18 module(s): CVS400 with earth leakage protection, direct with long terminal shield
	enclosure)
	18 module(s): CVS400 with earth leakage protection , direct with long terminal shield in 600 mm Widefloor-standing enclosure (cable coming from top or bottom of
	enclosure)
	shield in 600 mm Widewall-mounted enclosure (cable coming from top or bottom of
	15 module(s): NSX630 without earth leakage protection , direct with long terminal
	enclosure)
	shield in 600 mm Widefloor-standing enclosure (cable coming from top or bottom of
	15 module(s): NSX630 without earth leakage protection , direct with long terminal
	enclosure)
	15 module(s): NSX400 without earth leakage protection , direct with long terminal shield in 600 mm Widewall-mounted enclosure (cable coming from top or bottom of
	enclosure)
	shield in 600 mm Widefloor-standing enclosure (cable coming from top or bottom of
	15 module(s): NSX400 without earth leakage protection , direct with long terminal
	enclosure)
	shield in 600 mm Widewall-mounted enclosure (cable coming from top or bottom of
	15 module(s): CVS630 without earth leakage protection , direct with long terminal
	enclosure)
	shield in 600 mm Widefloor-standing enclosure (cable coming from top or bottom of
	enclosure) 15 module(s): CVS630 without earth leakage protection , direct with long terminal
	shield in 600 mm Widewall-mounted enclosure (cable coming from top or bottom of
	15 module(s): CVS400 without earth leakage protection , direct with long terminal
	enclosure)
lm]	shield in 600 mm Widefloor-standing enclosure (cable coming from top or bottom of

Complementary

Cable Entry	Cut-out plates 0.31 mm top or bottom 267 mm Cut-out plates 0.312 mm top or bottom 317 mm
Protective Treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Surface Finish	Smooth Matt
Colour	White (RAL 9001)
Width	600 mm
Height	500 mm
Net Weight	2.24 kg

Functional Unit

600 mm Prisma G floor-standing enclosure EasyPact CVS400 without fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 15 0.31 mm 600 mm Prisma G wall-mounted enclosure EasyPact CVS400 without fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 15 0.31 mm 600 mm Prisma G floor-standing enclosure EasyPact CVS400 without fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 15 0.31 mm 600 mm Prisma G wall-mounted enclosure EasyPact CVS400 without fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 15 0.31 mm 600 mm Prisma G floor-standing enclosure EasyPact CVS630 without fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 15 0.31 mm 600 mm Prisma G wall-mounted enclosure EasyPact CVS630 without fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 15 0.31 mm 600 mm Prisma G floor-standing enclosure EasyPact CVS630 without fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 15 0.31 mm 600 mm Prisma G wall-mounted enclosure EasyPact CVS630 without fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 15 0.31 mm 600 mm Prisma G floor-standing enclosure ComPact NSX400 without fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 15 0.31 mm 600 mm Prisma G wall-mounted enclosure ComPact NSX400 without fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 15 0.31 mm 600 mm Prisma G floor-standing enclosure ComPact NSX400 without fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 15 0.31 mm 600 mm Prisma G wall-mounted enclosure ComPact NSX400 without fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 15 0.31 mm 600 mm Prisma G floor-standing enclosure ComPact NSX630 without fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 15 0.31 mm 600 mm Prisma G wall-mounted enclosure ComPact NSX630 without fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 15 0.31 mm 600 mm Prisma G floor-standing enclosure ComPact NSX630 without fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 15 0.31 mm 600 mm Prisma G wall-mounted enclosure ComPact NSX630 without fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 15 0.31 mm 600 mm Prisma G floor-standing enclosure EasyPact CVS400 with fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 18 0.312 mm 600 mm Prisma G wall-mounted enclosure EasyPact CVS400 with fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 18 0.312 mm 600 mm Prisma G floor-standing enclosure EasyPact CVS400 with fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 18 0.312 mm 600 mm Prisma G wall-mounted enclosure EasyPact CVS400 with fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 18 0.312 mm 600 mm Prisma G floor-standing enclosure EasyPact CVS630 with fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 18 0.312 mm 600 mm Prisma G wall-mounted enclosure EasyPact CVS630 with fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 18 0.312 mm 600 mm Prisma G floor-standing enclosure EasyPact CVS630 with fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 18 0.312 mm 600 mm Prisma G wall-mounted enclosure EasyPact CVS630 with fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 18 0.312 mm 600 mm Prisma G floor-standing enclosure ComPact NSX400 with fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 18 0.312 mm 600 mm Prisma G wall-mounted enclosure ComPact NSX400 with fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 18 0.312 mm 600 mm Prisma G floor-standing enclosure ComPact NSX400 with fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 18 0.312 mm 600 mm Prisma G wall-mounted enclosure ComPact NSX400 with fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 18 0.312 mm 600 mm Prisma G floor-standing enclosure ComPact NSX630 with fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 18 0.312 mm 600 mm Prisma G wall-mounted enclosure ComPact NSX630 with fixed direct front rotary handle vertical 3P 1 direct with long terminal shield 18 0.312 mm 600 mm Prisma G floor-standing enclosure ComPact NSX630 with fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 18 0.312 mm 600 mm Prisma G wall-mounted enclosure ComPact NSX630 with fixed direct front rotary handle vertical 4P 1 direct with long terminal shield 18 0.312 mm

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.500 cm
Package 1 Width	23.000 cm
Package 1 Length	47.000 cm
Package 1 Weight	2.240 kg

Unit Type Of Package 2	S04
Number Of Units In Package 2	9
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	20.260 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	36
Package 3 Height	45.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	80.740 kg

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes
Halogen Free Plastic Parts Product

Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile